

PRINTER TYPE	PRINTING METHOD	Impact dot matrix																						
	PRINT DIRECTION	Bi-directional printing with logic seeking																						
	INPUT DATA BUFFER	64K or 0KByte (selectable)																						
CONSUMABLES	RIBBON CARTRIDGE BLACK	Fabric Ribbon Cartridge 8 million characters (LQ 10 cpi, 48 dots/character)																						
DIMENSIONS	WIDTH x DEPTH x HEIGHT	639 x 402 x 257mm																						
	WEIGHT	Approx. 13kg																						
PRINT SPEED		<ul style="list-style-type: none"> <li>High speed draft 10 cpi</li> <li>Draft 15 cpi</li> <li>Draft 12 cpi</li> <li>Draft 10 cpi</li> <li>Draft 20 cpi condensed</li> <li>Draft 17 cpi condensed</li> <li>LQ 15 cpi</li> <li>LQ 12 cpi</li> <li>LQ 10 cpi</li> <li>LQ 20 cpi condensed</li> <li>LQ 17 cpi condensed</li> </ul>	480 cps 539 cps 431 cps 360 cps 359 cps 308 cps 179 cps 143 cps 120 cps 238 cps 204 cps																					
RELIABILITY	PRINT HEAD LIFE	400 million strokes/wire																						
	MVBF (Mean Print Volume Between Failure)	24 Millions lines (except print head)																						
	MTBF (Mean Print Volume Between Failure)	<ul style="list-style-type: none"> <li>10,000 POH (25% duty cycle)</li> <li>7.5 million lines (except print head)</li> </ul>																						
PRINT CHARACTERISTICS	CHARACTER SETS	<ul style="list-style-type: none"> <li>1 Legal character set</li> <li>35 international character sets</li> <li>13 character code tables: Italic, PC437, PC850, PC860, PC861, PC863, PC865, Abicomp, BRASC II, Roman 8, ISO Latin 1, PC858, ISO 8859-15</li> </ul>																						
	BITMAP FONTS	<ul style="list-style-type: none"> <li>EPSON Draft: 10, 12, 15 cpi</li> <li>EPSON Roman: 10, 12, 15 cpi, Proportional</li> <li>EPSON Sans Serif: 10, 12, 15 cpi, Proportional</li> <li>EPSON Courier: 10, 12, 15 cpi</li> <li>EPSON Prestige: 10, 12 cpi</li> <li>EPSON Script: 10 cpi</li> <li>EPSON OCR-B: 10 cpi</li> <li>EPSON Orator: 10 cpi</li> <li>EPSON Orator S: 10 cpi</li> <li>EPSON Script C: Proportional</li> </ul>																						
	SCALABLE FONTS	<ul style="list-style-type: none"> <li>EPSON Roman: 8 to 32 pts</li> <li>EPSON Sans Serif: 8 to 32 pts</li> <li>EPSON Roman T: 8 to 32 pts</li> <li>EPSON Sans Serif H: 8 to 32 pts</li> </ul>																						
	BAR CODE FONTS	EAN-13, EAN-8, Interleaved 2 of 5, UPC-A, UPC-E, Code 39, Code 128, PostNet																						
PRINTABLE COLUMNS	CHARACTERS PER LINE PITCH (CPI)	<table border="1"> <thead> <tr> <th></th> <th>Characters per line</th> <th>Characters</th> </tr> </thead> <tbody> <tr> <td>Pitch (cpi)</td> <td></td> <td></td> </tr> <tr> <td>• 10 cpi</td> <td>136</td> <td>10</td> </tr> <tr> <td>• 12 cpi</td> <td>163</td> <td>12</td> </tr> <tr> <td>• 15 cpi</td> <td>204</td> <td>15</td> </tr> <tr> <td>• 17 cpi Condensed</td> <td>233</td> <td>17.1</td> </tr> <tr> <td>• 20 cpi Condensed</td> <td>272</td> <td>20</td> </tr> </tbody> </table>		Characters per line	Characters	Pitch (cpi)			• 10 cpi	136	10	• 12 cpi	163	12	• 15 cpi	204	15	• 17 cpi Condensed	233	17.1	• 20 cpi Condensed	272	20	
	Characters per line	Characters																						
Pitch (cpi)																								
• 10 cpi	136	10																						
• 12 cpi	163	12																						
• 15 cpi	204	15																						
• 17 cpi Condensed	233	17.1																						
• 20 cpi Condensed	272	20																						
CONTROL PANEL		7 switches, 10 LEDs																						
PRINTER DRIVER/UTILITY	PRINTER DRIVER	<ul style="list-style-type: none"> <li>Microsoft® Windows® version 3.1</li> <li>Microsoft® Windows® version 95/98</li> <li>Microsoft® Windows® NT® 3.51/4.0</li> </ul>																						
	PRINTER UTILITY	EPSON Remote! (MS-DOS environment only)																						
INTERFACE	STANDARD	• Bi-directional parallel interface (IEEE-P1284)																						
	OPTION	<ul style="list-style-type: none"> <li>Type B Serial Interface</li> <li>Type B 32KB Intelligent Serial Interface Card</li> <li>Type B 32KB Intelligent Parallel Interface Card</li> <li>Type B 32KB IEEE-488 Interface Card</li> <li>Type B Interface Card For LocalTalk™</li> <li>Type B Coax Interface Card</li> <li>Type B Twinax Interface Card</li> <li>Type B Ethernet® (10 Base 2/T)</li> <li>Type B Ethernet® (10 Base 2/T)</li> <li>Type B Ethernet® (100 Base TX)*</li> <li>AC adapter for: Type B Ethernet® Interface Card (100 Base TX)</li> </ul> <p>* Regional AC Adapter Set (C825253) is required</p>	C823061 C823081 C823102 C823132 C823122 C823142 C823152 C823573 C823623 C823633 C825253																					
PAPER HANDLING	PAPER PATH	Standard <ul style="list-style-type: none"> <li>Manual insertion: Front in, Top out Rear in, Top out</li> <li>Tractor: Front in, Top out Rear in, Top out Bottom in, Top out</li> </ul> Option <ul style="list-style-type: none"> <li>Cut Sheet Feeder Rear in, Top out</li> </ul>																						
	CUT SHEET SIZE	<ul style="list-style-type: none"> <li>Width: 100 - 420mm (3.9 - 16.5")</li> <li>Length: Front in 148 - 420mm (5.8 - 16.5") Rear in 100 - 420mm (3.9 - 16.5")</li> </ul>																						
	ENVELOPES	No.6, No.10																						
	CONTINUOUS PAPER SIZE	<ul style="list-style-type: none"> <li>Width: 101 - 406mm (4.0 - 16.0")</li> <li>Length: Max 559mm (22.0")</li> </ul> * Allows label printing																						
	PAPER THICKNESS	<ul style="list-style-type: none"> <li>Cut Sheet Single Sheet: 0.065 - 0.14mm (0.0025 - 0.0055")</li> <li>Multi-part sheets 0.12 - 0.39mm (0.0047 - 0.018")</li> <li>Envelopes: 0.16 - 0.52mm (0.0063 - 0.0205")</li> <li>Continuous Paper Single Sheet/Multi-part forms 0.065 - 0.46mm (0.0025-0.018")</li> <li>Continuous Forms With Labels Base Sheet 0.07 - 0.09mm (0.0028 - 0.0035") Total Sheet 0.16 - 0.19mm (0.0063 - 0.0075")</li> </ul>																						
	PAPER FEEDING	<ul style="list-style-type: none"> <li>Friction Feed (Front/Rear )</li> <li>Push Tractor Feed (Front/Rear)</li> <li>Push-Pull Tractor (Front/Rear)</li> <li>Pull Tractor (Front/Rear/Bottom)</li> </ul>																						
	COPIES	Original + 5 copies																						
	LINE SPACING	1/6" or programmable by 1/360"																						
ACOUSTIC NOISE		Approx. 54dB (A) (ISO 7779 pattern)																						
POWER REQUIREMENTS	VOLTAGE	220 - 240V																						
	RATED FREQUENCY	50 - 60 Hz																						
	POWER CONSUMPTION	Approx. 52W (ISO 10561 Letter Pattern) Energy Star Compliant																						
ENVIRONMENTAL CONDITIONS	TEMPERATURE	10 - 35° C																						
	HUMIDITY	10 - 80% RH																						
OPTIONS		<ul style="list-style-type: none"> <li>Pull Tractor Unit</li> <li>Roll Paper Holder</li> <li>High Capacity Cut Sheet Feeder</li> <li>Second-Bin Cut Sheet Feeder*</li> </ul> <p>* Second-Bin Cut Sheet Feeder cannot be provided without ordering High Capacity Cut Sheet Feeder</p>	C800322 #8310 C806732 C806742																					